

P/N NAS662C0-8

Description

flat head

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information


SKU / Model: NAS662C08

Minimum Qty (MOQ): 50


NSN: 5305-01-076-8100

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









^{*} See page 2 for technical characteristics

P/N NAS662C0-8 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.426 Inches Minimum And 0.475 Inches Maximum
Fastener Length:	0.470 Inches Minimum And 0.500 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.105 Inches Minimum And 0.119 Inches Maximum
Internal Drive Style:	Slot
Nominal Thread Diameter:	0.060 Inches
Thread Quantity Per Inch:	80
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Steel Comp 321 Or Steel Comp 347 Or Steel Comp 303 Or Steel Comp 303se Or Steel Comp 302
Screw Material Document And Classification:	Qq-s-763 Fed Spec 1st Material Response Or Qq-s-763 Fed Spec 2nd Material Response Or Astm A582 Assn Std 3rd Material Response Or Astm A582 Assn Std 4th Material Response Or Mil-s-7720 Mil Spec 5th Material Response
Screw Surface Treatment:	Passivate
Screw Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response
Thread Series Designator:	Unf
Specification/standard Data:	80205-nas662 Professional/industrial Association Standard

How to Order

Order this machine screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/NAS662C0-8 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.