

Description

NAS662C0R3 Machine Screw

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS662C0R3
Minimum Qty (MOQ):	100
NSN:	5305-01-073-1475
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS662C0R3 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.108 Inches Minimum And 0.169 Inches Maximum
Fastener Length:	0.158 Inches Minimum And 0.188 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.105 Inches Minimum And 0.119 Inches Maximum
Internal Drive Style:	Cross Recess Type Ii
Nominal Thread Diameter:	0.060 Inches
Thread Quantity Per Inch:	80
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Steel Comp 321 Or Steel Comp 347 Or Steel Comp 303se Or Steel Comp 302
Screw Surface Treatment:	Passivate
Screw Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response
Thread Series Designator:	Unf
Specification/standard Data:	80205-nas662 Professional/industrial Association Standard

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS662C0R3> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.