

Description

NAS662C2-2 Machine Screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS662C22
Minimum Qty (MOQ):	25
NSN:	5305-00-275-8269
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS662C2-2 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.023 Inches Minimum And 0.096 Inches Maximum
Fastener Length:	0.095 Inches Minimum And 0.125 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.156 Inches Minimum And 0.172 Inches Maximum
Internal Drive Style:	Slot
Nominal Thread Diameter:	0.086 Inches
Thread Quantity Per Inch:	56
Minimum Tensile Strength:	55000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material Document And Classification:	Mil-s-7720 Mil Spec 1st Material Response Or Mil-s-7720 Comp 303s Mil Spec 2nd Material Response Or Qq-s-763 Class 8 Type A Fed Spec 3rd Material Response Or Qq-s-763 Class 8 Type A Fed Spec 4th Material Response
Screw Surface Treatment:	Passivate
Screw Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response
Thread Series Designator:	Unc
Specification/standard Data:	80205-nas662 Professional/industrial Association Standard

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS662C2-2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.