

Description

Fastener Length: 5/16", Thread: 2-56, Thread Length: 9/32", NAS662 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS662C25
Minimum Qty (MOQ):	25
NSN:	5305-01-023-6227
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N NAS662C2-5 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.210 Inches Minimum And 0.282 Inches Maximum
Fastener Length:	0.282 Inches Minimum And 0.312 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.156 Inches Minimum And 0.172 Inches Maximum
Internal Drive Style:	Slot
Nominal Thread Diameter:	0.086 Inches
Thread Quantity Per Inch:	56
Minimum Tensile Strength:	60000 Pounds Per Square Inch
Countersink Angle:	100.0 Degrees Nominal
Screw Material:	Steel Comp 304l Or Steel Comp 316l Or Steel Comp 302 Or Steel Comp 347 Or Steel Comp 321 Or Steel Comp 317 Or Steel Comp 316 Or Steel Comp 310 Or Steel Comp 309 Or Steel Comp 305 Or Steel Comp 304
Screw Surface Treatment:	Passivate
Screw Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response
Thread Series Designator:	Unc
Specification/standard Data:	80205-nas662 Professional/industrial Association Standard

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS662C2-5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.