

**Description**

Fastener Length: 1/8", Thread: 2-56, Thread Length: 3/32"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS662C2LER2
Minimum Qty (MOQ):	5 EA
NSN:	5305-00-145-0984
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N NAS662C2LER2 Specifications

<b>Thread Class:</b>	2a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.023 Inches Minimum And 0.096 Inches Maximum
<b>Fastener Length:</b>	0.095 Inches Minimum And 0.125 Inches Maximum
<b>Head Style:</b>	Flat Countersunk
<b>Head Diameter:</b>	0.156 Inches Minimum And 0.172 Inches Maximum
<b>Locking Feature:</b>	Pellet Threads Or Strip Threads
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>Nominal Thread Diameter:</b>	0.086 Inches
<b>Thread Quantity Per Inch:</b>	56
<b>Minimum Tensile Strength:</b>	80000 Pounds Per Square Inch
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Material:</b>	Steel Comp 303 Overall
<b>Material Document And Classification:</b>	Qq-s-764 Fed Spec Single Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unc

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS662C2LER2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.