

## P/N NAS662C2LER5

## **Description**

Fastener Length: 5/16", Thread: 2-56, Thread Length: 9/32",

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS662C2LER5

Minimum Qty (MOQ): 10

NSN: 5305-00-182-9506

Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS662C2LER5 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.210 Inches Minimum And 0.283 Inches Maximum
Fastener Length:	0.282 Inches Minimum And 0.312 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.156 Inches Minimum And 0.172 Inches Maximum
Locking Feature:	Pellet Threads Or Strip Threads
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.086 Inches
Thread Quantity Per Inch:	56
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Material:	Steel Comp 302 Overall Or Steel Comp 303 Overall Or Steel Comp 321 Overall Or Steel Comp 347 Overall
Material Document And Classification:	Mil-s-7720 Mil Spec 1st Material Response Overall Or Astm A582 Assn Std 2nd Material Response Overall Or Qq-s-763 Class 321 Fed Spec 3rd Material Response Overall Or Qq-s-763 Class 347 Fed Spec 4th Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unc
Specification/standard Data:	80205-nas662 Professional/industrial Association Standard

### **How to Order**

Order this shear bolt from our inventory online by visiting <a href="https://military-fasteners.com/bolts/shear+bolts/NAS662C2LER5">https://military-fasteners.com/bolts/shear+bolts/NAS662C2LER5</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.