

P/N NAS662C2LER9

Description

Fastener Length: 9/16", Thread: 2-56, Thread Length: 17/32

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: NAS662C2LER9

Minimum Qty (MOQ):

NSN: 5305-00-119-7687

Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









P/N NAS662C2LER9 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.496 Inches Minimum And 0.533 Inches Maximum
Fastener Length:	0.532 Inches Minimum And 0.562 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.156 Inches Minimum And 0.172 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.086 Inches
Thread Quantity Per Inch:	56
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unc
Specification/standard Data:	80205-nas662 Professional/industrial Association Standard

How to Order

Order this socket head cap screw from our inventory online by visiting https://military-fasteners.com/screws/socket+head+cap+screws/NAS662C2LER9 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.