

## P/N NAS662C2LLR4

## **Description**

Fastener Length: 1/4", Thread: 2-56, Thread Length: 1/4

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS662C2LLR4

Minimum Qty (MOQ): 20

NSN: 5305-00-827-2799

Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# **P/N NAS662C2LLR4 Specifications**

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.250 Inches Minimum
Fastener Length:	0.250 Inches Nominal
Head Style:	Flat Countersunk
Head Diameter:	0.156 Inches Minimum And 0.172 Inches Maximum
Locking Feature:	Strip Threads
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.086 Inches
Thread Quantity Per Inch:	56
Countersink Angle:	100.0 Degrees Nominal
Material:	Steel Corrosion Resisting Overall
Surface Treatment:	Passivate Overall
Thread Series Designator:	Unc
Specification/standard Data:	80205-nas662 Professional/industrial Association Standard

### **How to Order**

Order this shear bolt from our inventory online by visiting <a href="https://military-fasteners.com/bolts/shear+bolts/NAS662C2LLR4">https://military-fasteners.com/bolts/shear+bolts/NAS662C2LLR4</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.