

Description

Fastener Length: 1/4", Thread: 2-56, Thread Length: 1/4

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS662C2LLR4
Minimum Qty (MOQ):	20
NSN:	5305-00-827-2799
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS662C2LLR4 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.250 Inches Minimum
Fastener Length:	0.250 Inches Nominal
Head Style:	Flat Countersunk
Head Diameter:	0.156 Inches Minimum And 0.172 Inches Maximum
Locking Feature:	Strip Threads
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.086 Inches
Thread Quantity Per Inch:	56
Countersink Angle:	100.0 Degrees Nominal
Material:	Steel Corrosion Resisting Overall
Surface Treatment:	Passivate Overall
Thread Series Designator:	Unc
Specification/standard Data:	80205-nas662 Professional/industrial Association Standard

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS662C2LLR4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.