

P/N NAS662C2R12

Description

Length: 0.75", flat countersunk head, NAS662 series screw

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: NAS662C2R12

Minimum Qty (MOQ): 100

NSN: 5305-00-043-0442

Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









^{*} See page 2 for technical characteristics

P/N NAS662C2R12 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.714 Inches Minimum
Fastener Length:	0.750 Inches Nominal
Head Style:	Flat Countersunk
Head Diameter:	0.156 Inches Minimum And 0.172 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.086 Inches
Thread Quantity Per Inch:	56
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Steel Corrosion Resisting
Screw Surface Treatment:	Passivate
Thread Series Designator:	Unc
Specification/standard Data:	80205-nas662 Professional/industrial Association Standard

How to Order

Order this machine screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/NAS662C2R12 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check outhere to complete your order.