

Description

Fastener Length: 15/16", Thread: 2-56, Thread Length: 29/32

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS662C2R15
Minimum Qty (MOQ):	5
NSN:	5305-00-138-9914
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	096640, Screws, Iron Or Steel



P/N NAS662C2R15 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.836 Inches Minimum And 0.909 Inches Maximum
Fastener Length:	0.908 Inches Minimum And 0.938 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.156 Inches Minimum And 0.175 Inches Maximum
Internal Drive Style:	Cross Recess Type 1
Nominal Thread Diameter:	0.086 Inches
Thread Quantity Per Inch:	56
Minimum Tensile Strength:	80000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Screw Material:	Steel Comp 302 Or Steel Comp 303 Or Steel Comp 321 Or Steel Comp 347
Screw Material Document And Classification:	Mil-s-7720 Mil Spec 1st Material Response Or Qq-s-764 Fed Spec 2nd Material Response Or Qq-s-763 Fed Spec 3rd Material Response Or Qq-s-763 Fed Spec 4th Material Response
Screw Surface Treatment:	Passivate
Screw Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response
Thread Series Designator:	Unc
Specification/standard Data:	80205-nas662 Professional/industrial Association Standard

How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS662C2R15> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.