

**Description**

Fastener Length: 15/16", Thread: 2-56, Thread Length: 29/32

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS662C2R15
Minimum Qty (MOQ):	5
NSN:	5305-00-138-9914
Schedule B:	7318.15.6080
ECCN:	9A991
National Motor Freight:	096640, Screws, Iron Or Steel



## P/N NAS662C2R15 Specifications

<b>Thread Class:</b>	2a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.836 Inches Minimum And 0.909 Inches Maximum
<b>Fastener Length:</b>	0.908 Inches Minimum And 0.938 Inches Maximum
<b>Head Style:</b>	Flat Countersunk
<b>Head Diameter:</b>	0.156 Inches Minimum And 0.175 Inches Maximum
<b>Internal Drive Style:</b>	Cross Recess Type 1
<b>Nominal Thread Diameter:</b>	0.086 Inches
<b>Thread Quantity Per Inch:</b>	56
<b>Minimum Tensile Strength:</b>	80000 Pounds Per Square Inch
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Screw Material:</b>	Steel Comp 302 Or Steel Comp 303 Or Steel Comp 321 Or Steel Comp 347
<b>Screw Material Document And Classification:</b>	Mil-s-7720 Mil Spec 1st Material Response Or Qq-s-764 Fed Spec 2nd Material Response Or Qq-s-763 Fed Spec 3rd Material Response Or Qq-s-763 Fed Spec 4th Material Response
<b>Screw Surface Treatment:</b>	Passivate
<b>Screw Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response
<b>Thread Series Designator:</b>	Unc
<b>Specification/standard Data:</b>	80205-nas662 Professional/industrial Association Standard

## How to Order

Order this machine screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/NAS662C2R15> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.