

**Description**

Fastener Length: 1-17/32", Thread: 10-32, Thread Length: 23/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |                                      |
|-------------------------|--------------------------------------|
| SKU / Model:            | NAS663V19HT                          |
| Minimum Qty (MOQ):      | 5 EA                                 |
| NSN:                    | 5305-01-044-8533                     |
| Schedule B:             | 8108.90.3060                         |
| ECCN:                   | 9A991                                |
| National Motor Freight: | 136500, Metal Noi / Metal Alloys Noi |

NO IMAGE  
AVAILABLE

## P/N NAS663V19HT Specifications

|                                              |                                                           |
|----------------------------------------------|-----------------------------------------------------------|
| <b>Thread Class:</b>                         | 3a                                                        |
| <b>Thread Direction:</b>                     | Right-hand                                                |
| <b>Thread Length:</b>                        | 0.314 Inches Minimum And 0.364 Inches Maximum             |
| <b>Fastener Length:</b>                      | 1.512 Inches Minimum And 1.542 Inches Maximum             |
| <b>Head Style:</b>                           | Flat Countersunk                                          |
| <b>Head Diameter:</b>                        | 0.339 Inches Minimum And 0.381 Inches Maximum             |
| <b>Grip Diameter:</b>                        | 0.1890 Inches Minimum And 0.1895 Inches Maximum           |
| <b>Internal Drive Style:</b>                 | High-torque                                               |
| <b>Nominal Thread Diameter:</b>              | 0.190 Inches                                              |
| <b>Grip Length:</b>                          | 1.178 Inches Minimum And 1.198 Inches Maximum             |
| <b>Thread Quantity Per Inch:</b>             | 32                                                        |
| <b>Minimum Tensile Strength:</b>             | 160000 Pounds Per Square Inch                             |
| <b>Countersink Angle:</b>                    | 100.0 Degrees Nominal                                     |
| <b>Surface Finish:</b>                       | 32.0 Microinches Grip                                     |
| <b>Surface Finish:</b>                       | 32.0 Microinches Threads                                  |
| <b>Material:</b>                             | Titanium Alloy Overall                                    |
| <b>Material Document And Classification:</b> | Nas 621 Assn Std Single Material Response Overall         |
| <b>Thread Series Designator:</b>             | Unjf                                                      |
| <b>Specification/standard Data:</b>          | 80205-nas663 Professional/Industrial Association Standard |

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS663V19HT> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.