

Description

Fastener Length: 19/32", Thread: 10-32, Thread Length: 23/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS663V4HT
Minimum Qty (MOQ):	5 EA
NSN:	5305-00-338-3254
National Motor Freight:	136500, Metal Noi / Metal Alloys Noi Sub1

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS663V4HT Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.314 Inches Minimum And 0.364 Inches Maximum
Fastener Length:	0.574 Inches Minimum And 0.604 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.339 Inches Minimum And 0.381 Inches Maximum
Grip Diameter:	0.1890 Inches Minimum And 0.1895 Inches Maximum
Internal Drive Style:	High-torque
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.240 Inches Minimum And 0.260 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Material:	Titanium Alloy Overall
Material Document And Classification:	Nas621 Comp 6al-4v Assn Std Single Material Response Overall Or Ams-4928 Assn Std Single Material Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas621 Professional/Industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS663V4HT> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.