

Description

Fastener Length: 21/32", Thread: 10-32, Thread Length: 23/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS663V5HT
Minimum Qty (MOQ):	10 EA
NSN:	5305-00-347-8294
National Motor Freight:	136500, Metal Noi / Metal Alloys Noi

NO IMAGE
AVAILABLE

P/N NAS663V5HT Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.314 Inches Minimum And 0.364 Inches Maximum
Fastener Length:	0.636 Inches Minimum And 0.666 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.339 Inches Minimum And 0.381 Inches Maximum
Grip Diameter:	0.1890 Inches Minimum And 0.1895 Inches Maximum
Internal Drive Style:	High-torque
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.302 Inches Minimum And 0.322 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Material:	Titanium Alloy Overall
Material Document And Classification:	Nas621 Comp 6al-4v Assn Std Single Material Response Overall Or Ams 4928 Assn Std Single Material Response Overall
Thread Series Designator:	Unf
Specification/standard Data:	80205-nas663 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS663V5HT> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.