

Description

NAS6703-16 Shear Bolt

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS670316
Minimum Qty (MOQ):	2
NSN:	5306-01-506-4055
ECCN:	EAR99
National Motor Freight:	093483, Bolts,nuts Or Screws,noi Iron Or



NO IMAGE
AVAILABLE

P/N NAS6703-16 Specifications

Thread Class:	2a
Thread Direction:	Right-hand
Thread Length:	0.345 Inches Nominal
Fastener Length:	1.345 Inches Nominal
Head Style:	Dished Hexagon
Head Height:	0.110 Inches Minimum And 0.125 Inches Maximum
Width Between Flats:	0.367 Inches Minimum And 0.376 Inches Maximum
Grip Diameter:	0.189 Inches Nominal
Nominal Thread Diameter:	0.190 Inches
Grip Length:	1.000 Inches Nominal
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	190000 Pounds Per Square Inch
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams5731 Assn Std Single Material Response Overall Or Ams5732 Assn Std Single Material Response Overall Or Ams5737 Assn Std Single Material Response Overall Or Ams5853 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416, Tyii, Cl2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6703-16> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.