

**Description**

Length: 15/32", Thread: 10-28, Thread Length: 11/32, hexagon head, tension, long thread, cadmium plated corrosion resistant/stainless steel

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model: NAS67032

Minimum Qty (MOQ): 20

NSN: 5306-01-186-4548

ECCN: EAR99

National Motor Freight: 096630, Screws Noi Brass / Bronze / Copper



\* See page 2 for technical characteristics

## P/N NAS6703-2 Specifications

|   |  |
|---|--|
| <b>Thread Class:</b>                                  | 3a   |
| <b>Thread Direction:</b>                              | Right-hand   |
| <b>Thread Length:</b>                                 | 0.345 Inches Nominal   |
| <b>Fastener Length:</b>                               | 0.460 Inches Minimum And 0.480 Inches Maximum  |
| <b>Head Style:</b>                                    | Dished Hexagon   |
| <b>Head Height:</b>                                   | 0.110 Inches Minimum And 0.125 Inches Maximum  |
| <b>Width Between Flats:</b>                           | 0.367 Inches Minimum And 0.376 Inches Maximum  |
| <b>Grip Diameter:</b>                                 | 0.1885 Inches Minimum And 0.1895 Inches Maximum  |
| <b>Nominal Thread Diameter:</b>                       | 0.190 Inches   |
| <b>Grip Length:</b>                                   | 0.115 Inches Minimum And 0.135 Inches Maximum  |
| <b>Thread Quantity Per Inch:</b>                      | 28   |
| <b>Material:</b>                                      | Iron Alloy 660 Overall   |
| <b>Material Document And Classification:</b>          | Ams 5731 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall |
| <b>Surface Treatment:</b>                             | Cadmium Overall  |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-35 Fed Spec Single Treatment Response Overall   |
| <b>Thread Series Designator:</b>                      | Unjf   |
| <b>Specification/standard Data:</b>                   | 80205-nas6703-2 Professional/industrial Association Standard   |

## How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6703-2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.