

P/N NAS6703-9

Military-Fasteners.com

Description

Fastener Length: 59/64", Thread: 10-32, Thread Length: 11/32

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	NAS67039
Minimum Qty (MOQ):	10
NSN:	5306-01-330-7081
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N NAS6703-9 Specifications

Thread Class:3aThread Direction:Right-handThread Length:0.345 Inches NominalFastener Length:0.892 Inches Minimum And 0.922 Inches MaximumHead Style:Dished HexagonHead Height:0.110 Inches Minimum And 0.125 Inches MaximumWidth Between Flats:0.367 Inches Minimum And 0.125 Inches MaximumOminal Thread Diameter:0.367 Inches Minimum And 0.1376 Inches MaximumNominal Thread Diameter:0.190 InchesOptimation:0.552 Inches Minimum And 0.572 Inches MaximumThread Quantity Per Inch:32Surface Finish:3.0.000 Pounds Per Square InchSurface Finish:3.0.000 Pounds Per Square InchSurface Finish:3.0.000 Founds Of HeadSurface Finish:3.0.000 Founds Per Square InchSurface Finish:3.0.0000 Founds Per Square InchSurface Finish:3.0.0000000000000000000000000000000000
Thread Length:0.345 Inches NominalFastener Length:0.892 Inches Minimum And 0.922 Inches MaximumHead Style:Dished HexagonHead Height:0.110 Inches Minimum And 0.125 Inches MaximumWidth Between Flats:0.367 Inches Minimum And 0.376 Inches MaximumGrip Diameter:0.1885 Inches Minimum And 0.1895 Inches MaximumNominal Thread Diameter:0.190 InchesGrip Length:0.552 Inches Minimum And 0.572 Inches MaximumThread Quantity Per Inch:32Surface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsSurface Finish:32.0 Microinches ThreadsSurface Finish:32.0 Microinches ThreadsSurface Finish:32.0 Microinches Threads
Fastener Length:0.892 Inches Minimum And 0.922 Inches MaximumHead Style:Dished HexagonHead Height:0.110 Inches Minimum And 0.125 Inches MaximumWidth Between Flats:0.367 Inches Minimum And 0.376 Inches MaximumGrip Diameter:0.1855 Inches Minimum And 0.1895 Inches MaximumNominal Thread Diameter:0.190 InchesGrip Length:0.552 Inches Minimum And 0.572 Inches MaximumThread Quantity Per Inch:32Minimum Tensile Strength:160000 Pounds Per Square InchSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches Strength:Surface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches CripSurface Finish:32.0 Microinches CripSurface Finish:32.0 Microinches Crip
Head Style:Dished HexagonHead Height:0.110 Inches Minimum And 0.125 Inches MaximumWidth Between Flats:0.367 Inches Minimum And 0.376 Inches MaximumGrip Diameter:0.1885 Inches Minimum And 0.1895 Inches MaximumNominal Thread Diameter:0.190 InchesGrip Length:0.552 Inches Minimum And 0.572 Inches MaximumThread Quantity Per Inch:32Minimum Tensile Strength:16000 Pounds Per Square InchSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsSurface Finish:32.0 Microinches ThreadsSurface Finish:32.0 Microinches Threads
Head Height:0.110 Inches Minimum And 0.125 Inches MaximumWidth Between Flats:0.367 Inches Minimum And 0.376 Inches MaximumGrip Diameter:0.1885 Inches Minimum And 0.1895 Inches MaximumNominal Thread Diameter:0.190 InchesGrip Length:0.552 Inches Minimum And 0.572 Inches MaximumThread Quantity Per Inch:32Minimum Tensile Strength:160000 Pounds Per Square InchSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches Threads
Width Between Flats:0.367 Inches Minimum And 0.376 Inches MaximumGrip Diameter:0.1885 Inches Minimum And 0.1895 Inches MaximumNominal Thread Diameter:0.190 InchesGrip Length:0.552 Inches Minimum And 0.572 Inches MaximumThread Quantity Per Inch:32Minimum Tensile Strength:16000 Pounds Per Square InchSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches Grip
Grip Diameter:0.1885 Inches Minimum And 0.1895 Inches MaximumNominal Thread Diameter:0.190 InchesGrip Length:0.552 Inches Minimum And 0.572 Inches MaximumThread Quantity Per Inch:32Minimum Tensile Strength:16000 Pounds Per Square InchSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches Grip
Nominal Thread Diameter:0.190 InchesGrip Length:0.552 Inches Minimum And 0.572 Inches MaximumThread Quantity Per Inch:32Minimum Tensile Strength:160000 Pounds Per Square InchSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches Grip
Grip Length:0.552 Inches Minimum And 0.572 Inches MaximumThread Quantity Per Inch:32Minimum Tensile Strength:160000 Pounds Per Square InchSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches Threads
Thread Quantity Per Inch:32Minimum Tensile Strength:160000 Pounds Per Square InchSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches Threads
Minimum Tensile Strength:160000 Pounds Per Square InchSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches Threads
Surface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches Threads
Surface Finish: 32.0 Microinches Grip Surface Finish: 32.0 Microinches Threads
Surface Finish: 32.0 Microinches Threads
Special Features: Dve Threads Only Green
Color: Green Threads
Material: Iron Alloy 660 Overall
Material Document And Classification:Ams 5731 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall
Surface Treatment: Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification: Ams 5731 Assn Std Single Treatment Response Overall Or Ams 5737 Assn Std Single Treatment Response Overall
Thread Series Designator: Unjf
Specification/standard Data: 80205-nas6703 Professional/industrial Association Standard

How to Order

Order this shear bolt from our inventory online by visiting <u>https://military-fasteners.com/bolts/shear+bolts/NAS6703-9</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.