

**Description**

Fastener Length: 39/64", Thread: 10-32, Thread Length: 23/64

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS6703A4                                 |
| Minimum Qty (MOQ):      | 10  |
| NSN:                    | 5306-01-206-7229                          |
| Schedule B:             | 7318.15.8085                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



## P/N NAS6703A4 Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>                                  | 3a  |
| <b>Thread Direction:</b>                              | Right-hand  |
| <b>Thread Length:</b>                                 | 0.320 Inches Minimum And 0.370 Inches Maximum                       |
| <b>Fastener Length:</b>                               | 0.580 Inches Minimum And 0.610 Inches Maximum                       |
| <b>Head Style:</b>                                    | Dished Hexagon  |
| <b>Head Height:</b>                                   | 0.110 Inches Minimum And 0.125 Inches Maximum                       |
| <b>Width Between Flats:</b>                           | 0.367 Inches Minimum And 0.376 Inches Maximum                       |
| <b>Grip Diameter:</b>                                 | 0.1885 Inches Minimum And 0.1895 Inches Maximum                     |
| <b>Nominal Thread Diameter:</b>                       | 0.190 Inches  |
| <b>Grip Length:</b>                                   | 0.240 Inches Minimum And 0.260 Inches Maximum                       |
| <b>Thread Quantity Per Inch:</b>                      | 32  |
| <b>Minimum Tensile Strength:</b>                      | 160000 Pounds Per Square Inch                                       |
| <b>Surface Finish:</b>                                | 32.0 Microinches Bearing Surface Of Head                            |
| <b>Surface Finish:</b>                                | 32.0 Microinches Grip   |
| <b>Surface Finish:</b>                                | 32.0 Microinches Threads  |
| <b>Material:</b>                                      | Iron Alloy 660 Overall  |
| <b>Material Document And Classification:</b>          | Ams 5737 Assn Std Single Material Response Overall                  |
| <b>Surface Treatment:</b>                             | Aluminum Overall  |
| <b>Surface Treatment Document And Classification:</b> | Bms 10-85 Ty 1 Fscm 81205 Mfr Ref Single Treatment Response Overall |
| <b>Thread Series Designator:</b>                      | Unf   |

## How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6703A4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.