P/N NAS6703A5

Description

Fastener Length: 43/64", Thread: 10-32, Thread Length: 11/32

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS6703A5
Minimum Qty (MOQ):	10
NSN:	5306-01-519-2349
Schedule B:	7318.15.8085
ECCN:	EAR99

* See page 2 for technical characteristics

P/N NAS6703A5 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.345 Inches Nominal
Fastener Length:	0.642 Inches Minimum And 0.672 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.110 Inches Minimum And 0.125 Inches Maximum
Width Between Flats:	0.367 Inches Minimum And 0.376 Inches Maximum
Grip Diameter:	0.1885 Inches Minimum And 0.1895 Inches Maximum
Single Shear Strength:	95000 Pounds Per Square Inch
End Item Identification:	Boeing B757 Aircraft
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.302 Inches Minimum And 0.322 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Sae-ams5731 Assn Std Single Material Response Overall Or Sae-ams5732 Assn Std Single Material Response Overall Or Sae-ams5737 Assn Std Single Material Response Overall Or Sae-ams5853 Assn Std Single Material Response Overall
Surface Treatment:	Aluminum Overall
Thread Series Designator:	Unjf

How to Order

Order this shear bolt from our inventory online by visiting https://military-fasteners.com/bolts/shear+bolts/NAS6703A5 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.