

Description

Fastener Length: 1-11/32", Thread: 10-32, Thread Length: 11/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS6703D14
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-575-9931
Schedule B:	7318.15.8085
ECCN:	EAR99

NO IMAGE
AVAILABLE

P/N NAS6703D14 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.345 Inches Nominal
Fastener Length:	1.315 Inches Minimum And 1.345 Inches Maximum
Head Style:	Hexagon
Head Height:	0.125 Inches Minimum And 0.140 Inches Maximum
Width Between Flats:	0.367 Inches Minimum And 0.376 Inches Maximum
Grip Diameter:	0.188 Inches Minimum And 0.189 Inches Maximum
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.875 Inches Nominal
Thread Quantity Per Inch:	32
Part Name Assigned By Controlling Agency:	Bolt, Tension, Hex Head, Close Tolerance, A286 Cres, Long Thread, Reduced Major Thread Diameter, Non-locking, 160 Ksi Ftu
Material:	Steel Corrosion Resisting Overall
Material Document And Classification:	Ams5731 Assn Std Single Material Response Overall Or Ams5732 Assn Std Single Material Response Overall Or Ams5737 Assn Std Single Material Response Overall Or Ams5853 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Ams-qq-p-416, Type 2, Class 2 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6703D14> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.