

Description

Fastener Length: 1-43/64", Thread: 10-32, Thread Length: 11/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS6703D21 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5306-01-585-5660 |
| Schedule B: | 7318.15.8085 |
| ECCN: | 9A991 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N NAS6703D21 Specifications

| | |
|---|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.345 Inches Nominal |
| Fastener Length: | 1.642 Inches Minimum And 1.672 Inches Maximum |
| Head Style: | Dished Hexagon |
| Head Height: | 0.110 Inches Minimum And 0.125 Inches Maximum |
| Width Between Flats: | 0.367 Inches Minimum And 0.376 Inches Maximum |
| Grip Diameter: | 0.188 Inches Minimum And 0.189 Inches Maximum |
| Shank Unthreaded Hole Diameter: | 0.070 Inches Nominal First Hole |
| Nominal Thread Diameter: | 0.190 Inches |
| Grip Length: | 1.302 Inches Minimum And 1.322 Inches Maximum |
| Thread Quantity Per Inch: | 32 |
| Minimum Tensile Strength: | 95000 Pounds Per Square Inch |
| Distance From Head Largest Bearing Surface To Shank Hole Center: | 2.681 Inches Nominal First Hole |
| Part Name Assigned By Controlling Agency: | Bolt Tension Hex Head Close Tolerance |
| Special Features: | Item Has Drilled Shank Bolt |
| Material: | Steel Corrosion Resisting Overall |
| Surface Treatment: | Passivate Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6703D21> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.