



Military-Fasteners.com

P/N NAS6703D26

Description

Fastener Length: 1-63/64", Thread: 10-32, Thread Length: 11/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS6703D26
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-572-6774
Schedule B:	7318.15.8085
ECCN:	9A991



* See page 2 for technical characteristics

P/N NAS6703D26 Specifications

Thread Direction:	Right-hand
Thread Length:	0.345 Inches Nominal
Fastener Length:	1.980 Inches Minimum And 2.105 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.110 Inches Minimum And 0.125 Inches Maximum
Width Between Flats:	0.367 Inches Minimum And 0.376 Inches Maximum
Grip Diameter:	0.189 Inches Nominal
Nominal Thread Diameter:	0.190 Inches
Grip Length:	1.615 Inches Minimum And 1.635 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Part Name Assigned By Controlling Agency:	Bolt,hex Head,close Tolerance,a286 Cres,long Threads,self-locking And Nonlocking
Material:	Steel Corrosion Resisting Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416, Ty 2. Cl 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt hex from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6703D26> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.