

Description

Fastener Length: 1-43/64", Thread: 10-32, Thread Length: 11/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS6703DU21
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-550-4071
Schedule B:	7318.15.2091
ECCN:	9A991



* See page 2 for technical characteristics

P/N NAS6703DU21 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.345 Inches Nominal
Fastener Length:	1.642 Inches Minimum And 1.672 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.110 Inches Minimum And 0.125 Inches Maximum
Width Between Flats:	0.367 Inches Minimum And 0.376 Inches Maximum
Grip Diameter:	0.189 Inches Nominal
Shank Unthreaded Hole Diameter:	0.070 Inches Minimum First Hole And 0.080 Inches Maximum First Hole
Nominal Thread Diameter:	0.190 Inches
Grip Length:	1.302 Inches Minimum And 1.322 Inches Maximum
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	1600000 Pounds Per Square Inch
Distance From Head Largest Bearing Surface To Shank Hole Center:	1.493 Inches Nominal First Hole
Material:	Steel Corrosion Resisting Overall
Material Document And Classification:	Ams5731 Assn Std 1st Material Response Overall And Ams35732 Assn Std 2nd Material Response Overall And Ams 5737 Assn Std 3rd Material Response Overall And Ams 5853 Assn Std 4th Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas6703 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6703DU21> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.