

Description

Fastener Length: 1-31/32", Hole Diameter: 3/16", Thread: 10-32, Thread Length: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS6703DU26
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-536-0751
Schedule B:	7318.15.8085
ECCN:	EAR99

NO IMAGE
AVAILABLE

P/N NAS6703DU26 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.306 Inches Nominal
Fastener Length:	1.970 Inches Nominal
Head Style:	Hexagon
Head Height:	0.110 Inches Nominal
Width Between Flats:	0.367 Inches Minimum And 0.376 Inches Maximum
Hole Diameter:	0.190 Inches Nominal
Grip Diameter:	0.1890 Inches Minimum And 0.1895 Inches Maximum
Point Diameter:	0.181 Inches Minimum And 0.184 Inches Maximum
Shank Unthreaded Hole Diameter:	0.070 Inches Nominal Overall
Point Style:	Flat
Nominal Thread Diameter:	0.190 Inches
Grip Length:	1.625 Inches Nominal
Hole Quantity:	1
Hole Type:	Drilled
Thread Quantity Per Inch:	32
Hole Configuration Style:	Hexagon Flats
Material:	Steel Corrosion Resisting Overall
Surface Treatment:	Passivate Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6703DU26> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.