

Description

Fastener Length: 1-31/32", Hole Diameter: 3/16", Thread: 10-32, Thread Length: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|--------------------|------------------|
| SKU / Model: | NAS6703DU26 |
| Minimum Qty (MOQ): | 1 EA |
| NSN: | 5306-01-536-0751 |
| Schedule B: | 7318.15.8085 |
| ECCN: | EAR99 |

NO IMAGE
AVAILABLE

P/N NAS6703DU26 Specifications

| | |
|--|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.306 Inches Nominal |
| Fastener Length: | 1.970 Inches Nominal |
| Head Style: | Hexagon |
| Head Height: | 0.110 Inches Nominal |
| Width Between Flats: | 0.367 Inches Minimum And 0.376 Inches Maximum |
| Hole Diameter: | 0.190 Inches Nominal |
| Grip Diameter: | 0.1890 Inches Minimum And 0.1895 Inches Maximum |
| Point Diameter: | 0.181 Inches Minimum And 0.184 Inches Maximum |
| Shank Unthreaded Hole Diameter: | 0.070 Inches Nominal Overall |
| Point Style: | Flat |
| Nominal Thread Diameter: | 0.190 Inches |
| Grip Length: | 1.625 Inches Nominal |
| Hole Quantity: | 1 |
| Hole Type: | Drilled |
| Thread Quantity Per Inch: | 32 |
| Hole Configuration Style: | Hexagon Flats |
| Material: | Steel Corrosion Resisting Overall |
| Surface Treatment: | Passivate Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6703DU26> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.