

**Description**

Fastener Length: 1-31/32", Hole Diameter: 3/16", Thread: 10-32, Thread Length: 1/4"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS6703DU26
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-536-0751
Schedule B:	7318.15.8085
ECCN:	EAR99

NO IMAGE  
AVAILABLE

## P/N NAS6703DU26 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.306 Inches Nominal
<b>Fastener Length:</b>	1.970 Inches Nominal
<b>Head Style:</b>	Hexagon
<b>Head Height:</b>	0.110 Inches Nominal
<b>Width Between Flats:</b>	0.367 Inches Minimum And 0.376 Inches Maximum
<b>Hole Diameter:</b>	0.190 Inches Nominal
<b>Grip Diameter:</b>	0.1890 Inches Minimum And 0.1895 Inches Maximum
<b>Point Diameter:</b>	0.181 Inches Minimum And 0.184 Inches Maximum
<b>Shank Unthreaded Hole Diameter:</b>	0.070 Inches Nominal Overall
<b>Point Style:</b>	Flat
<b>Nominal Thread Diameter:</b>	0.190 Inches
<b>Grip Length:</b>	1.625 Inches Nominal
<b>Hole Quantity:</b>	1
<b>Hole Type:</b>	Drilled
<b>Thread Quantity Per Inch:</b>	32
<b>Hole Configuration Style:</b>	Hexagon Flats
<b>Material:</b>	Steel Corrosion Resisting Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6703DU26> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.