

P/N NAS6703DU3

Military-Fasteners.com

Description

Fastener Length: 35/64", Thread: 10-32, Thread Length: 23/64"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model:	NAS6703DU3	
Minimum Qty (MOQ):	5 EA	
NSN:	5306-01-310-3645	
Schedule B:	7318.15.8085	
ECCN:	9A991	
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)	



P/N NAS6703DU3 Specifications

Thread Direction:Right-handThread Length:0.320 Inches Minimum And 0.370 Inches MaximumFastener Length:0.518 Inches Minimum And 0.548 Inches MaximumHead Style:Dished HexagonHead Height:0.110 Inches Minimum And 0.125 Inches MaximumWidth Between Flats:0.367 Inches Minimum And 0.376 Inches MaximumGrip Diameter:0.1890 Inches Minimum And 0.1895 Inches MaximumShank Unthreaded Hole Diameter:0.190 Inches Minimum And 0.1895 Inches Maximum First HoleNominal Thread Diameter:0.190 Inches Minimum And 0.198 Inches Maximum First HoleNominal Thread Diameter:0.190 InchesNominal Thread Diameter:0.190 InchesMinimum Tensile Strength:0.190 InchesDistance From Head Largest Bearing Surface To Shank Hole Center:0.156 Inches Minimum First Hole And 0.186 Inches Maximum First HoleSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches ThreadsSurface Finish:32.0 Microinches ThreadsMaterial Document And Classification:Ams5737 Assn Std Single Material Response OverallMaterial Document And Classification:Qa-p-35 Fed Spec Single Treatment Response OverallThread Series Designator:Unjf		2
Thread Length:0.320 Inches Minimum And 0.370 Inches MaximumFastener Length:0.518 Inches Minimum And 0.548 Inches MaximumHead Style:Dished HexagonHead Style:0.110 Inches Minimum And 0.125 Inches MaximumWidth Between Flats:0.367 Inches Minimum And 0.125 Inches MaximumGrip Diameter:0.367 Inches Minimum And 0.1895 Inches MaximumShark Unthreaded Hole Diameter:0.100 Inches Minimum And 0.1895 Inches Maximum First HoleNominal Thread Diameter:0.170 Inches Minimum And 0.1895 Inches Maximum First HoleNominal Thread Diameter:0.170 Inches Minimum And 0.1895 Inches Maximum First HoleNominal Thread Diameter:0.170 Inches Minimum And 0.198 Inches Maximum First HoleOrigi Length:0.178 Inches Minimum And 0.198 Inches MaximumThread Quartity Per Inch:32Minimum Tensile Strength:0.156 Inches Minimum First Hole And 0.186 Inches Maximum First HoleDistance From Head Largest Bearing Surface To Shank Hole Center:0.156 Inches Minimum First Hole And 0.186 Inches Maximum First HoleSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsMaterial Document And Classification:Ams5737 Assn Std Single Material Response OverallSurface Treatment:Saviet OverallMaterial Document And Classification:Oq-p.35 Fed Spec Single Treatment Response Overall	Thread Class:	
Fastener Length:0.518 Inches Minimum And 0.548 Inches MaximumHead Style:Dished HexagonHead Height:0.110 Inches Minimum And 0.125 Inches MaximumWidth Between Flats:0.367 Inches Minimum And 0.376 Inches MaximumGrip Diameter:0.3670 Inches Minimum And 0.376 Inches MaximumShank Unthreaded Hole Diameter:0.1900 Inches Minimum And 0.1895 Inches Maximum First HoleNominal Thread Diameter:0.1900 Inches Minimum And 0.198 Inches Maximum First HoleOrip Length:0.178 Inches Minimum And 0.198 Inches Maximum First HoleThread Quantity Per Inch:32Surface From Head Largest Bearing Surface To Shank Hole Center:0.156 Inches Minimum First Hole And 0.186 Inches Maximum First HoleSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface	Thread Direction:	Right-hand
Head Style:Dished HexagonHead Height:0.110 Inches Minimum And 0.125 Inches MaximumWidth Between Flats:0.367 Inches Minimum And 0.376 Inches MaximumGrip Diameter:0.1890 Inches Minimum And 0.1895 Inches Maximum First HoleShank Unthreaded Hole Diameter:0.070 Inches Minimum First Hole And 0.080 Inches Maximum First HoleNominal Thread Diameter:0.190 InchesGrip Length:0.178 Inches Minimum And 0.198 Inches MaximumThread Quantity Per Inch:32Minimum Tensile Strength:160000 Pounds Per Square InchDistance From Head Largest Bearing Surface To Shank Hole Center:0.156 Inches Minimum First Hole And 0.186 Inches Maximum First HoleSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsMaterial Document And Classification:Ams5737 Assn Std Single Material Response OverallSurface Treatment:0q-p-35 Fed Spec Single Treatment Response OverallThread Series Designator:Unjf	Thread Length:	0.320 Inches Minimum And 0.370 Inches Maximum
Head Height:0.110 Inches Minimum And 0.125 Inches MaximumWidth Between Flats:0.367 Inches Minimum And 0.376 Inches MaximumGrip Diameter:0.1890 Inches Minimum And 0.1895 Inches Maximum First HoleShank Unthreaded Hole Diameter:0.070 Inches Minimum First Hole And 0.080 Inches Maximum First HoleNominal Thread Diameter:0.190 InchesOrip Length:0.178 Inches Minimum And 0.198 Inches MaximumThread Quantity Per Inch:32Minimum Tensile Strength:0.156 Inches Minimum First Hole And 0.186 Inches Maximum First HoleDistance From Head Largest Bearing Surface To Shank Hole Center:0.156 Inches Minimum First Hole And 0.186 Inches Maximum First HoleSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsMaterial Document And Classification:Ams5737 Assn Std Single Material Response OverallMaterial Document And Classification:Oq-p-35 Fed Spec Single Treatment Response OverallThread Series Designator:Unjf	Fastener Length:	0.518 Inches Minimum And 0.548 Inches Maximum
Width Between Flats:0.367 Inches Minimum And 0.376 Inches MaximumGrip Diameter:0.1890 Inches Minimum And 0.1895 Inches Maximum First HoleShank Unthreaded Hole Diameter:0.070 Inches Minimum First Hole And 0.080 Inches Maximum First HoleNominal Thread Diameter:0.190 InchesGrip Length:0.178 Inches Minimum And 0.198 Inches MaximumThread Quantity Per Inch:32Minimum Tensile Strength:16000 Pounds Per Square InchDistance From Head Largest Bearing Surface To Shank Hole Center:0.156 Inches Minimum First Hole And 0.186 Inches Maximum First HoleSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsMaterial Document And Classification:Ams5737 Assn Std Single Material Response OverallMaterial Document And Classification:Q-p-35 Fed Spec Single Treatment Response OverallMateriae Document And Classification:Oq-p-55 Fed Spec Single Treatment Response OverallMateriae Document And Classification:Oq-p-55 Fed Spec Single Treatment Response OverallMateriae Document And Classification:Oq-p-55 Fed Spec Single Treatment Response OverallMateriae Document And Classification:Oq-p-55 Fed Spec Single Treatment Response OverallMateriae Document And Classification:Oq-p-55 Fed Spec Single Treatment Response Overall	Head Style:	Dished Hexagon
Grip Dameter:0.1890 Inches Minimum And 0.1895 Inches MaximumShank Unthreaded Hole Diameter:0.070 Inches Minimum First Hole And 0.080 Inches Maximum First HoleNominal Thread Diameter:0.190 InchesGrip Length:0.178 Inches Minimum And 0.198 Inches MaximumThread Quantity Per Inch:32Distance From Head Largest Bearing Surface To Shank Hole Center:0.156 Inches Minimum First Hole And 0.186 Inches Maximum First HoleSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsMaterial:Iron Alloy 660 OverallMaterial Document And Classification:Ams5737 Assn Std Single Material Response OverallSurface Treatment:Oq-p-35 Fed Spec Single Treatment Response OverallMaterial Document And Classification:Unjf	Head Height:	0.110 Inches Minimum And 0.125 Inches Maximum
Shark Unthreaded Hole Diameter:0.070 Inches Minimum First Hole And 0.080 Inches Maximum First HoleNominal Thread Diameter:0.190 InchesGrip Length:0.178 Inches Minimum And 0.198 Inches MaximumThread Quantity Per Inch:32Minimum Tensile Strength:160000 Pounds Per Square InchDistance From Head Largest Bearing Surface To Shank Hole Center:0.156 Inches Minimum First Hole And 0.186 Inches Maximum First HoleSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsMaterial Document And Classification:Minist Hole OverallSurface Treatment:Qu-p-35 Fed Spec Single Treatment Response OverallSurface Freatment Document And Classification:Unjf	Width Between Flats:	0.367 Inches Minimum And 0.376 Inches Maximum
Nominal Thread Diameter:0.190 InchesGrip Length:0.178 Inches Minimum And 0.198 Inches MaximumThread Quantity Per Inch:32Minimum Tensile Strength:160000 Pounds Per Square InchDistance From Head Largest Bearing Surface To Shank Hole Center:0.156 Inches Minimum First Hole And 0.186 Inches Maximum First HoleSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsMaterial:Iron Alloy 660 OverallMaterial Document And Classification:Passivate OverallSurface Treatment:Q-p-35 Fed Spec Single Treatment Response OverallSurface Treatment Document And Classification:Unjf	Grip Diameter:	0.1890 Inches Minimum And 0.1895 Inches Maximum
Grip Length:0.178 Inches Minimum And 0.198 Inches MaximumThread Quantity Per Inch:32Minimum Tensile Strength:60000 Pounds Per Square InchDistance From Head Largest Bearing Surface To Shank Hole Center:0.156 Inches Minimum First Hole And 0.186 Inches Maximum First HoleSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsSurface Finish:Non Alloy 660 OverallMaterial Document And Classification:Ams5737 Assn Std Single Material Response OverallSurface Treatment:Oq-p-35 Fed Spec Single Treatment Response OverallMaterial Document And Classification:Nif	Shank Unthreaded Hole Diameter:	0.070 Inches Minimum First Hole And 0.080 Inches Maximum First Hole
Thread Quantity Per Inch:32Minimum Tensile Strength:160000 Pounds Per Square InchDistance From Head Largest Bearing Surface To Shank Hole Center:0.156 Inches Minimum First Hole And 0.186 Inches Maximum First HoleSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsMaterial:Iron Alloy 660 OverallMaterial Document And Classification:Ams5737 Assn Std Single Material Response OverallSurface Treatment:Qq-p-35 Fed Spec Single Treatment Response OverallMaterial Document And Classification:Document And Classification:Surface Treatment Document And Classification:Unjf	Nominal Thread Diameter:	0.190 Inches
Minimum Tensile Strength:160000 Pounds Per Square InchDistance From Head Largest Bearing Surface To Shank Hole Center:0.156 Inches Minimum First Hole And 0.186 Inches Maximum First HoleSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsMaterial:Iron Alloy 660 OverallMaterial Document And Classification:Ams5737 Assn Std Single Material Response OverallSurface Treatment:OverallSurface Treatment Document And Classification:OverallSurface Treatment Document And Classification:Overall<	Grip Length:	0.178 Inches Minimum And 0.198 Inches Maximum
Distance From Head Largest Bearing Surface To Shank Hole Center:0.156 Inches Minimum First Hole And 0.186 Inches Maximum First HoleSurface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsMaterial:Iron Alloy 660 OverallMaterial Document And Classification:Ams5737 Assn Std Single Material Response OverallSurface Treatment:Passivate OverallSurface Treatment Document And Classification:Urg -p35 Fed Spec Single Treatment Response OverallUnjfUnjf	Thread Quantity Per Inch:	32
Surface Finish:32.0 Microinches Bearing Surface Of HeadSurface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsMaterial:100 Alloy 660 OverallMaterial Document And Classification:Ams5737 Assn Std Single Material Response OverallSurface Treatment:Passivate OverallSurface Treatment Document And Classification:Qq-p-35 Fed Spec Single Treatment Response OverallUnjfUnjf	Minimum Tensile Strength:	160000 Pounds Per Square Inch
Surface Finish:32.0 Microinches GripSurface Finish:32.0 Microinches ThreadsMaterial:iron Alloy 660 OverallMaterial Document And Classification:Ams5737 Assn Std Single Material Response OverallSurface Treatment:Passivate OverallSurface Treatment Document And Classification:Qq-p-35 Fed Spec Single Treatment Response OverallDurface Treatment:Document And Classification:Surface Treatment Document And Classification:Document And Classification:Durface Treatment Document And Classification:Document And Classification:Durface Treatment Document And Classification:Document And Spec Single Treatment Response OverallDurface Treatment Document And Classification:Document And Spec Single Treatment Response OverallDurface Treatment Document And Classification:Document And Spec Single Treatment Response OverallDurface Treatment Document And Classification:Document And Spec Single Treatment Response OverallDurface Treatment Response Document And Classification:Document And Spec Single Treatment Response OverallDurface Treatment Response Document And Spec Single Treatment Response OverallDurface Treatment Response Overall	Distance From Head Largest Bearing Surface To Shank Hole Center:	0.156 Inches Minimum First Hole And 0.186 Inches Maximum First Hole
Surface Finish:32.0 Microinches ThreadsMaterial:Iron Alloy 660 OverallMaterial Document And Classification:Ams5737 Assn Std Single Material Response OverallSurface Treatment:Passivate OverallSurface Treatment Document And Classification:Qq-p-35 Fed Spec Single Treatment Response OverallDescription:Description:Material Description:Description:Material Document And Classification:Description:Material Document And Classification:Description:Material Document And Classification:Description:Material Document And Classification:Description:Material Description:Description:Material Description:Description:<	Surface Finish:	32.0 Microinches Bearing Surface Of Head
Material: Iron Alloy 660 Overall Material Document And Classification: Ams5737 Assn Std Single Material Response Overall Surface Treatment: Passivate Overall Surface Treatment Document And Classification: Qq-p-35 Fed Spec Single Treatment Response Overall Thread Series Designator: Unjf	Surface Finish:	32.0 Microinches Grip
Material Document And Classification: Ams5737 Assn Std Single Material Response Overall Surface Treatment: Passivate Overall Surface Treatment Document And Classification: Qq-p-35 Fed Spec Single Treatment Response Overall Thread Series Designator: Unjf	Surface Finish:	32.0 Microinches Threads
Surface Treatment: Passivate Overall Surface Treatment Document And Classification: Qq-p-35 Fed Spec Single Treatment Response Overall Thread Series Designator: Unjf	Material:	Iron Alloy 660 Overall
Surface Treatment Document And Classification: Qq-p-35 Fed Spec Single Treatment Response Overall Thread Series Designator: Unjf	Material Document And Classification:	Ams5737 Assn Std Single Material Response Overall
Thread Series Designator: Unjf	Surface Treatment:	Passivate Overall
	Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Specification/standard Data: 80205-nas6703 Professional/industrial Association Standard	Thread Series Designator:	Unjf
	Specification/standard Data:	80205-nas6703 Professional/industrial Association Standard

How to Order

Order this bolt from our inventory online by visiting <u>https://military-fasteners.com/bolts/shear+bolts/NAS6703DU3</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.