

**Description**

Fastener Length: 59/64", Thread: 10-32, Thread Length: 23/64

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                    |                  |
|--------------------|------------------|
| SKU / Model:       | NAS6703DU9       |
| Minimum Qty (MOQ): | 5                |
| NSN:               | 5306-01-310-3646 |
| ECCN:              | EAR99            |

NO IMAGE  
AVAILABLE

## P/N NAS6703DU9 Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>  | 3a  |
| <b>Thread Direction:</b>  | Right-hand  |
| <b>Thread Length:</b>   | 0.320 Inches Minimum And 0.370 Inches Maximum                       |
| <b>Fastener Length:</b>   | 0.892 Inches Minimum And 0.922 Inches Maximum                       |
| <b>Head Style:</b>  | Dished Hexagon  |
| <b>Head Height:</b>   | 0.110 Inches Minimum And 0.125 Inches Maximum                       |
| <b>Width Between Flats:</b>   | 0.367 Inches Minimum And 0.376 Inches Maximum                       |
| <b>Grip Diameter:</b>   | 0.1890 Inches Minimum And 0.1895 Inches Maximum                     |
| <b>Shank Unthreaded Hole Diameter:</b>                                  | 0.070 Inches Minimum First Hole And 0.080 Inches Maximum First Hole |
| <b>Nominal Thread Diameter:</b>   | 0.190 Inches  |
| <b>Grip Length:</b>   | 0.552 Inches Minimum And 0.572 Inches Maximum                       |
| <b>Thread Quantity Per Inch:</b>  | 32  |
| <b>Minimum Tensile Strength:</b>  | 160000 Pounds Per Square Inch                                       |
| <b>Distance From Head Largest Bearing Surface To Shank Hole Center:</b> | 0.728 Inches Minimum First Hole And 0.758 Inches Maximum First Hole |
| <b>Surface Finish:</b>  | 32.0 Microinches Bearing Surface Of Head                            |
| <b>Surface Finish:</b>  | 32.0 Microinches Grip   |
| <b>Surface Finish:</b>  | 32.0 Microinches Threads  |
| <b>Material:</b>  | Iron Alloy 660 Overall  |
| <b>Material Document And Classification:</b>                            | Ams5737 Assn Std Single Material Response Overall                   |
| <b>Surface Treatment:</b>   | Passivate Overall   |
| <b>Surface Treatment Document And Classification:</b>                   | Qq-p-35 Fed Spec Single Treatment Response Overall                  |
| <b>Thread Series Designator:</b>  | Unjf  |
| <b>Specification/standard Data:</b>                                     | 80205-nas6703 Professional/industrial Association Standard          |

## How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6703DU9> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.