

Description

Fastener Length: 15/32", Thread Length: 11/32

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS6703H2
Minimum Qty (MOQ):	5
NSN:	5306-01-524-0779
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS6703H2 Specifications

Thread Direction:	Right-hand
Thread Length:	0.345 Inches Nominal
Fastener Length:	0.470 Inches Nominal
Head Style:	Dished Hexagon
Head Height:	0.110 Inches Minimum And 0.125 Inches Maximum
Width Between Flats:	0.410 Inches Nominal
Grip Diameter:	0.189 Inches Nominal
End Item Identification:	Nha Pre-provisioning Support Item
Grip Length:	0.115 Inches Minimum And 0.135 Inches Maximum
Criticality Code Justification:	Agav
Part Name Assigned By Controlling Agency:	Bolt, Hex Head, Close Tolerance, A286 Cres, Long Threads, Self-locking And Nonlocking
Material:	Iron Alloy 660 Overall
Surface Treatment:	Cadmium Overall
Thread Series Designator:	Unjf

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6703H2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.