

P/N NAS6703H2

Description

Fastener Length: 15/32", Thread Length: 11/32

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: NAS6703H2

Minimum Qty (MOQ): 5

NSN: 5306-01-524-0779

Schedule B: 7318.15.8085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









P/N NAS6703H2 Specifications

Thread Direction:	Right-hand
Thread Length:	0.345 Inches Nominal
Fastener Length:	0.470 Inches Nominal
Head Style:	Dished Hexagon
Head Height:	0.110 Inches Minimum And 0.125 Inches Maximum
Width Between Flats:	0.410 Inches Nominal
Grip Diameter:	0.189 Inches Nominal
End Item Identification:	Nha Pre-provisioning Support Item
Grip Length:	0.115 Inches Minimum And 0.135 Inches Maximum
Criticality Code Justification:	Agav
Part Name Assigned By Controlling Agency:	Bolt, Hex Head, Close Tolerence, A286 Cres, Long Threads, Self-locking And Nonlocking
Material:	Iron Alloy 660 Overall
Surface Treatment:	Cadmium Overall
Thread Series Designator:	Unjf

How to Order

Order this shear bolt from our inventory online by visiting https://military-fasteners.com/bolts/shear+bolts/NAS6703H2 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/shear+bolts/NAS6703H2 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/shear+bolts/NAS6703H2 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/shear+bolts/NAS6703H2 and selecting the quantity you want then click "add to cart".