

Description

Fastener Length: 15/32", Thread Length: 11/32

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS6703H2 |
| Minimum Qty (MOQ): | 5 |
| NSN: | 5306-01-524-0779 |
| Schedule B: | 7318.15.8085 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N NAS6703H2 Specifications

| | |
|--|---|
| Thread Direction: | Right-hand |
| Thread Length: | 0.345 Inches Nominal |
| Fastener Length: | 0.470 Inches Nominal |
| Head Style: | Dished Hexagon |
| Head Height: | 0.110 Inches Minimum And 0.125 Inches Maximum |
| Width Between Flats: | 0.410 Inches Nominal |
| Grip Diameter: | 0.189 Inches Nominal |
| End Item Identification: | Nha Pre-provisioning Support Item |
| Grip Length: | 0.115 Inches Minimum And 0.135 Inches Maximum |
| Criticality Code Justification: | Agav |
| Part Name Assigned By Controlling Agency: | Bolt, Hex Head, Close Tolerance, A286 Cres, Long Threads, Self-locking And Nonlocking |
| Material: | Iron Alloy 660 Overall |
| Surface Treatment: | Cadmium Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6703H2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.