

P/N NAS6703HU19

Description

Fastener Length: 1-17/32", Hole Diameter: 3/64", Thread: 10-32, Thread Length: 11/32"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: NAS6703HU19

Minimum Qty (MOQ): 5 EA

NSN: 5306-01-542-2822

Schedule B: 7318.15.8085

ECCN: 9A991

National Motor Freight: 093490, Bolt / Nut / Screw / Clips / Fastener / Etc



^{*} See page 2 for technical characteristics

P/N NAS6703HU19 Specifications

Thread Class:	За
Thread Direction:	Right-hand
Thread Length:	0.345 Inches Nominal
Fastener Length:	1.533 Inches Nominal
Head Style:	Dished Hexagon
Head Height:	0.110 Inches Minimum And 0.125 Inches Maximum
Width Between Flats:	0.367 Inches Minimum And 0.376 Inches Maximum
Hole Diameter:	0.046 Inches Minimum And 0.056 Inches Maximum
Grip Diameter:	0.1890 Inches Minimum And 0.1895 Inches Maximum
End Item Identification:	C-17a Aircraft
Nominal Thread Diameter:	0.1900 Inches
Grip Length:	1.188 Inches Nominal
Hole Quantity:	3
Hole Type:	Drilled
Thread Quantity Per Inch:	32
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Hole Configuration Style:	Hexagon Longitudinal Hole
Part Name Assigned By Controlling Agency:	Bolt,shear
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams5731 Assn Std Single Material Response Overall Or Ams5737 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting https://military-fasteners.com/bolts/shear+bolts/NAS6703HU19 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.