

Description

Fastener Length: 43/64", Hole Diameter: 1/32", Thread: 10-32, Thread Length: 11/64

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS6703HU5
Minimum Qty (MOQ):	5
NSN:	5306-01-237-5739
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N NAS6703HU5 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.181 Inches Minimum And 0.184 Inches Maximum
Fastener Length:	0.642 Inches Minimum And 0.672 Inches Maximum
Head Style:	Hexagon
Head Height:	0.110 Inches Minimum And 0.125 Inches Maximum
Width Between Flats:	0.410 Inches Nominal
Hole Diameter:	0.046 Inches Nominal
Grip Diameter:	0.1890 Inches Minimum And 0.1895 Inches Maximum
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.302 Inches Minimum And 0.322 Inches Maximum
Hole Quantity:	3
Hole Type:	Drilled
Thread Quantity Per Inch:	32
Hole Configuration Style:	Hexagon Corners
Material:	Iron Alloy 660 Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas6703hu5 Professional/industrial Association Standard

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6703HU5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.