

**Description**

Fastener Length: 43/64", Hole Diameter: 1/32", Thread: 10-32, Thread Length: 11/64

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS6703HU5                                |
| Minimum Qty (MOQ):      | 5   |
| NSN:                    | 5306-01-237-5739                          |
| Schedule B:             | 7318.15.8085                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

## P/N NAS6703HU5 Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>                                  | 3a  |
| <b>Thread Direction:</b>                              | Right-hand  |
| <b>Thread Length:</b>                                 | 0.181 Inches Minimum And 0.184 Inches Maximum                 |
| <b>Fastener Length:</b>                               | 0.642 Inches Minimum And 0.672 Inches Maximum                 |
| <b>Head Style:</b>                                    | Hexagon   |
| <b>Head Height:</b>                                   | 0.110 Inches Minimum And 0.125 Inches Maximum                 |
| <b>Width Between Flats:</b>                           | 0.410 Inches Nominal  |
| <b>Hole Diameter:</b>                                 | 0.046 Inches Nominal  |
| <b>Grip Diameter:</b>                                 | 0.1890 Inches Minimum And 0.1895 Inches Maximum               |
| <b>Nominal Thread Diameter:</b>                       | 0.190 Inches  |
| <b>Grip Length:</b>                                   | 0.302 Inches Minimum And 0.322 Inches Maximum                 |
| <b>Hole Quantity:</b>                                 | 3   |
| <b>Hole Type:</b>                                     | Drilled   |
| <b>Thread Quantity Per Inch:</b>                      | 32  |
| <b>Hole Configuration Style:</b>                      | Hexagon Corners   |
| <b>Material:</b>                                      | Iron Alloy 660 Overall  |
| <b>Surface Treatment:</b>                             | Passivate Overall   |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-35 Fed Spec Single Treatment Response Overall            |
| <b>Thread Series Designator:</b>                      | Unjf  |
| <b>Specification/standard Data:</b>                   | 80205-nas6703hu5 Professional/industrial Association Standard |

## How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6703HU5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.