

**Description**

Fastener Length: 43/64", Thread: 10-32, Thread Length: 23/64",

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | NAS6703U5                                 |
| Minimum Qty (MOQ):      | 25  |
| NSN:                    | 5306-01-131-9828                          |
| Schedule B:             | 7318.15.8085                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



## P/N NAS6703U5 Specifications

|   |  |
|---|--|
| <b>Thread Class:</b>                                  | 3a   |
| <b>Thread Direction:</b>                              | Right-hand   |
| <b>Thread Length:</b>                                 | 0.320 Inches Minimum And 0.370 Inches Maximum              |
| <b>Fastener Length:</b>                               | 0.642 Inches Minimum And 0.672 Inches Maximum              |
| <b>Head Style:</b>                                    | Dished Hexagon   |
| <b>Head Height:</b>                                   | 0.110 Inches Minimum And 0.125 Inches Maximum              |
| <b>Width Between Flats:</b>                           | 0.367 Inches Minimum And 0.376 Inches Maximum              |
| <b>Grip Diameter:</b>                                 | 0.1890 Inches Minimum And 0.1895 Inches Maximum            |
| <b>Nominal Thread Diameter:</b>                       | 0.190 Inches   |
| <b>Grip Length:</b>                                   | 0.302 Inches Minimum And 0.322 Inches Maximum              |
| <b>Thread Quantity Per Inch:</b>                      | 32   |
| <b>Minimum Tensile Strength:</b>                      | 160000 Pounds Per Square Inch                              |
| <b>Surface Finish:</b>                                | 32.0 Microinches Bearing Surface Of Head                   |
| <b>Surface Finish:</b>                                | 32.0 Microinches Grip                                      |
| <b>Surface Finish:</b>                                | 32.0 Microinches Threads                                   |
| <b>Material:</b>                                      | Iron Alloy 660 Overall                                     |
| <b>Material Document And Classification:</b>          | Ams 5731 Assn Std Single Material Response Overall         |
| <b>Surface Treatment:</b>                             | Passivate Overall  |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-35 Fed Spec Single Treatment Response Overall         |
| <b>Thread Series Designator:</b>                      | Unjf   |
| <b>Specification/standard Data:</b>                   | 80205-nas6703 Professional/industrial Association Standard |

## How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6703U5> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.