

**Description**

Fastener Length: 1-1/2", Thread: 1/4-28, Thread Length: 27/64

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	NAS670417
Minimum Qty (MOQ):	10
NSN:	5306-01-240-4029
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



## P/N NAS6704-17 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.425 Inches Nominal
<b>Fastener Length:</b>	1.472 Inches Minimum And 1.502 Inches Maximum
<b>Head Style:</b>	Hexagon
<b>Head Height:</b>	0.125 Inches Minimum And 0.140 Inches Maximum
<b>Width Between Flats:</b>	0.480 Inches Nominal
<b>Grip Diameter:</b>	0.2490 Inches Minimum And 0.2495 Inches Maximum
<b>Nominal Thread Diameter:</b>	0.250 Inches
<b>Grip Length:</b>	1.052 Inches Minimum And 1.072 Inches Maximum
<b>Thread Quantity Per Inch:</b>	28
<b>Surface Finish:</b>	32.0 Microinches Bearing Surface Of Head
<b>Material:</b>	Iron Alloy 660 Overall
<b>Surface Treatment:</b>	Cadmium Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-416 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf
<b>Specification/standard Data:</b>	80205-nas6704-17 Professional/industrial Association Standard

## How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6704-17> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.