

Description

length: 1.613", grip: 1.188", thread: 1/4-28, hex head - tension - long thread - cadmium plated corrosion resistant steel"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS670419
Minimum Qty (MOQ):	10
NSN:	5306-01-338-8151
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N NAS6704-19 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.425 Inches Nominal
Fastener Length:	1.598 Inches Minimum And 1.628 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.125 Inches Minimum And 0.140 Inches Maximum
Width Between Flats:	0.429 Inches Minimum And 0.439 Inches Maximum
Grip Diameter:	0.2485 Inches Minimum And 0.2495 Inches Maximum
Nominal Thread Diameter:	0.250 Inches
Grip Length:	1.178 Inches Minimum And 1.198 Inches Maximum
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams5731 Assn Std Single Material Response Overall Or Ams5737 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty2 Cl2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf
Specification/standard Data:	80205-nas6704 Professional/Industrial Association Standard

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6704-19> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.