

Description

Fastener Length: 1-15/16", Thread: 1/4-28, Thread Length: 3/8

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS670424
Minimum Qty (MOQ):	5
NSN:	5306-01-109-1338
Schedule B:	7318.15.8085
ECCN:	EAR99



P/N NAS6704-24 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.375 Inches Nominal
Fastener Length:	1.938 Inches Nominal
Head Style:	Dished Hexagon
Head Height:	0.132 Inches Nominal
Width Between Flats:	0.438 Inches Nominal
Grip Diameter:	0.2485 Inches Minimum And 0.2495 Inches Maximum
Shank Unthreaded Hole Diameter:	0.070 Inches Nominal First Hole
Nominal Thread Diameter:	0.250 Inches
Grip Length:	1.562 Inches Nominal
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Distance From Head Largest Bearing Surface To Shank Hole Center:	1.750 Inches Nominal First Hole
Material:	Steel Corrosion Resisting Overall
Thread Series Designator:	Unf

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6704-24> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.