

## P/N NAS6704-24

### **Description**

Fastener Length: 1-15/16", Thread: 1/4-28, Thread Length: 3/8

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS670424

Minimum Qty (MOQ):

NSN: 5306-01-109-1338

Schedule B: 7318.15.8085

ECCN: EAR99









<sup>\*</sup> See page 2 for technical characteristics

# P/N NAS6704-24 Specifications

| Thread Class:  | За  |
|--|---|
| Thread Direction:  | Right-hand                                      |
| Thread Length:   | 0.375 Inches Nominal                            |
| Fastener Length:   | 1.938 Inches Nominal                            |
| Head Style:  | Dished Hexagon                                  |
| Head Height:   | 0.132 Inches Nominal                            |
| Width Between Flats:   | 0.438 Inches Nominal                            |
| Grip Diameter:   | 0.2485 Inches Minimum And 0.2495 Inches Maximum |
| Shank Unthreaded Hole Diameter:                                  | 0.070 Inches Nominal First Hole                 |
| Nominal Thread Diameter:   | 0.250 Inches                                    |
| Grip Length:   | 1.562 Inches Nominal                            |
| Thread Quantity Per Inch:  | 28  |
| Minimum Tensile Strength:  | 160000 Pounds Per Square Inch                   |
| Distance From Head Largest Bearing Surface To Shank Hole Center: | 1.750 Inches Nominal First Hole                 |
| Material:  | Steel Corrosion Resisting Overall               |
| Thread Series Designator:  | Unf   |

## **How to Order**

Order this shear bolt from our inventory online by visiting <a href="https://military-fasteners.com/bolts/shear+bolts/NAS6704-24">https://military-fasteners.com/bolts/shear+bolts/NAS6704-24</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.