

**Description**

Fastener Length: 1-15/16", Thread: 1/4-28, Thread Length: 3/8

\* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	NAS670424
Minimum Qty (MOQ):	5
NSN:	5306-01-109-1338
Schedule B:	7318.15.8085
ECCN:	EAR99



## P/N NAS6704-24 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.375 Inches Nominal
<b>Fastener Length:</b>	1.938 Inches Nominal
<b>Head Style:</b>	Dished Hexagon
<b>Head Height:</b>	0.132 Inches Nominal
<b>Width Between Flats:</b>	0.438 Inches Nominal
<b>Grip Diameter:</b>	0.2485 Inches Minimum And 0.2495 Inches Maximum
<b>Shank Unthreaded Hole Diameter:</b>	0.070 Inches Nominal First Hole
<b>Nominal Thread Diameter:</b>	0.250 Inches
<b>Grip Length:</b>	1.562 Inches Nominal
<b>Thread Quantity Per Inch:</b>	28
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Distance From Head Largest Bearing Surface To Shank Hole Center:</b>	1.750 Inches Nominal First Hole
<b>Material:</b>	Steel Corrosion Resisting Overall
<b>Thread Series Designator:</b>	Unf

## How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6704-24> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.