

P/N NAS6704-3

Description

length: 0.613, grip: 0.188", thread: 1/4-28, hex head, tension, long thread, cadmium plated corrosion resistant steel

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: NAS67043

Minimum Qty (MOQ):

NSN: 5306-01-006-5461

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









P/N NAS6704-3 Specifications

3a
Right-hand
0.400 Inches Minimum And 0.450 Inches Maximum
0.593 Inches Minimum And 0.628 Inches Maximum
Hexagon
0.125 Inches Minimum And 0.140 Inches Maximum
0.430 Inches Minimum And 0.439 Inches Maximum
0.051 Inches Nominal
0.2485 Inches Minimum And 0.2495 Inches Maximum
0.250 Inches
0.178 Inches Minimum And 0.198 Inches Maximum
3
Drilled
28
160000 Pounds Per Square Inch
Hexagon Corners
Iron Alloy 660 Overall
Ams5731 Assn Std Single Material Response Overall
Cadmium Overall And Chromate Overall Or Chromium Overall
Qq-p-416 Ty 2 Cl 2 Fed Spec 1st Treatment Response Overall Or Qq-c-320 Cl 2 Fed Spec 2nd Treatment Response Overall
Unjf
80205-nas6704 Professional/industrial Association Standard

How to Order

Order this shear bolt from our inventory online by visiting https://military-fasteners.com/bolts/shear+bolts/NAS6704-3 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/shear+bolts/NAS6704-3 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/shear+bolts/NAS6704-3 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out https://military-fasteners.com/bolts/shear+bolts/NAS6704-3 and selecting the quantity you want then click "add to cart".