

Description

Thread: 1/4-28, Thread Length: 3/8",

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | NAS670442 |
| Minimum Qty (MOQ): | 2 |
| NSN: | 5306-01-479-9574 |
| Schedule B: | 7318.15.8085 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N NAS6704-42 Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.425 Inches Maximum |
| Fastener Length: | 3.035 Inches Minimum And 3.065 Inches Maximum |
| Head Style: | Hexagon |
| Head Height: | 0.125 Inches Minimum And 0.135 Inches Maximum |
| Width Between Flats: | 0.429 Inches Minimum And 0.439 Inches Maximum |
| Grip Diameter: | 0.2490 Inches Minimum And 0.2495 Inches Maximum |
| Nominal Thread Diameter: | 0.250 Inches |
| Grip Length: | 2.615 Inches Minimum And 2.635 Inches Maximum |
| Thread Quantity Per Inch: | 28 |
| Color: | Green Threads |
| Material: | Iron Alloy 660 Overall |
| Material Document And Classification: | Ams5731,ams5732 Assn Std 1st Material Response Overall Or Ams5853 Assn Std 2nd Material Response Overall |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Qq-p-416,type2,class2 Fed Spec 1st Treatment Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6704-42> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.