

# P/N NAS6704-46

## **Description**

Fastener Length: 3-5/16", Hole Diameter: ", Thread: 1/4-28, Thread Length: 27/64

\* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

## Order this part online

#### **Additional Information**

SKU / Model: NAS670446

Minimum Qty (MOQ):

NSN: 5306-01-479-9569

Schedule B: 7318.15.2091

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)









# P/N NAS6704-46 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.425 Inches Maximum
Fastener Length:	3.285 Inches Minimum And 3.315 Inches Maximum
Head Style:	Hexagon
Head Height:	0.125 Inches Minimum And 0.135 Inches Maximum
Width Between Flats:	0.429 Inches Minimum And 0.439 Inches Maximum
Hole Diameter:	0.010 Inches Maximum
Grip Diameter:	0.2490 Inches Minimum And 0.2495 Inches Maximum
Nominal Thread Diameter:	0.250 Inches
Grip Length:	2.865 Inches Minimum And 2.885 Inches Maximum
Hole Quantity:	3
Hole Type:	Drilled
Thread Quantity Per Inch:	28
Hole Configuration Style:	Hexagon Corners
Color:	Green Threads
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams5731,ams5732 Assn Std 1st Material Response Overall Or Ams5853 Assn Std 2nd Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,type2,class2 Fed Spec 1st Treatment Response Overall
Thread Series Designator:	Unjf

### **How to Order**

Order this shear bolt from our inventory online by visiting <a href="https://military-fasteners.com/bolts/shear+bolts/NAS6704-46">https://military-fasteners.com/bolts/shear+bolts/NAS6704-46</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.