

Description

length: 0.80", grip: 0.375", thread: 1/4-28, hex head, tension, long thread, cadmium plated corrosion resistant steel, NAS6704 series bolt

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS67046
Minimum Qty (MOQ):	20
NSN:	5306-01-478-6437
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N NAS6704-6 Specifications

Thread Class:	3a
Thread Length:	0.425 Inches Maximum
Fastener Length:	1.215 Inches Minimum And 1.235 Inches Maximum
Head Style:	Hexagon
Head Height:	0.480 Inches Minimum
Width Between Flats:	0.429 Inches Minimum And 0.439 Inches Maximum
Grip Diameter:	0.2490 Inches Minimum And 0.2495 Inches Maximum
Nominal Thread Diameter:	0.250 Inches
Grip Length:	0.790 Inches Minimum And 0.810 Inches Maximum
Thread Quantity Per Inch:	28
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams5731,ams5732,ams5737 Assn Std 1st Material Response Overall Or Ams5353 Assn Std 2nd Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,type2,class2 Fed Spec 1st Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6704-6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.