

Description

Fastener Length: 1-43/64", Thread: 1/4-28, Thread Length: 27/64", NAS6704 series bolt

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|--------------------|------------------|
| SKU / Model: | NAS6704D20 |
| Minimum Qty (MOQ): | 5 |
| NSN: | 5306-01-577-5602 |
| Schedule B: | 7318.15.8085 |
| ECCN: | EAR99 |



P/N NAS6704D20 Specifications

| | |
|---|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.425 Inches Nominal |
| Fastener Length: | 1.675 Inches Nominal |
| Head Style: | Dished Hexagon |
| Head Height: | 0.125 Inches Nominal |
| Width Between Flats: | 0.429 Inches Minimum And 0.439 Inches Maximum |
| Grip Diameter: | 0.2485 Inches Minimum And 0.2495 Inches Maximum |
| Shank Unthreaded Hole Diameter: | 0.076 Inches Nominal First Hole |
| Nominal Thread Diameter: | 0.2500 Inches |
| Grip Length: | 1.250 Inches Nominal |
| Thread Quantity Per Inch: | 28 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Distance From Head Largest Bearing Surface To Shank Hole Center: | 1.497 Inches Nominal First Hole |
| Special Features: | .2500-28 Thread Unjf-3a |
| Color: | Green Threads |
| Material: | Iron Alloy 660 Fastener |
| Material: | Plastic Polyamide Locking Feature |
| Surface Treatment: | Cadmium And Chromate Fastener |
| Thread Series Designator: | Unjf |

How to Order

Order this shear bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6704D20> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.