

Description

Fastener Length: 2-35/64", Thread: 1/4-28, Thread Length: 27/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS6704D34
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-581-1924
Schedule B:	7318.15.8085
ECCN:	EAR99

NO IMAGE
AVAILABLE

P/N NAS6704D34 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.425 Inches Nominal
Fastener Length:	2.550 Inches Nominal
Head Style:	Dished Hexagon
Head Height:	0.125 Inches Nominal
Width Between Flats:	0.429 Inches Minimum And 0.439 Inches Maximum
Grip Diameter:	0.2485 Inches Minimum And 0.2495 Inches Maximum
Shank Unthreaded Hole Diameter:	0.076 Inches Nominal First Hole
Nominal Thread Diameter:	0.2500 Inches
Grip Length:	2.125 Inches Nominal
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Distance From Head Largest Bearing Surface To Shank Hole Center:	2.372 Inches Nominal First Hole
Part Name Assigned By Controlling Agency:	Bolt, Tension, Hex Head
Special Features:	Close Tolerance, A286, Cres, Long Thread, Reduced Major Thread Dia, Self Locking And Non Locking 160 Ksi FtU
Color:	Green Threads
Material:	Iron Alloy 660 Overall
Surface Treatment:	Cadmium And Chromate Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6704D34> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.