



Military-Fasteners.com

P/N NAS6704D34

Description

Fastener Length: 2-35/64", Thread: 1/4-28, Thread Length: 27/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS6704D34
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-581-1924
Schedule B:	7318.15.8085
ECCN:	EAR99



\* See page 2 for technical characteristics

## P/N NAS6704D34 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.425 Inches Nominal
<b>Fastener Length:</b>	2.550 Inches Nominal
<b>Head Style:</b>	Dished Hexagon
<b>Head Height:</b>	0.125 Inches Nominal
<b>Width Between Flats:</b>	0.429 Inches Minimum And 0.439 Inches Maximum
<b>Grip Diameter:</b>	0.2485 Inches Minimum And 0.2495 Inches Maximum
<b>Shank Unthreaded Hole Diameter:</b>	0.076 Inches Nominal First Hole
<b>Nominal Thread Diameter:</b>	0.2500 Inches
<b>Grip Length:</b>	2.125 Inches Nominal
<b>Thread Quantity Per Inch:</b>	28
<b>Minimum Tensile Strength:</b>	160000 Pounds Per Square Inch
<b>Distance From Head Largest Bearing Surface To Shank Hole Center:</b>	2.372 Inches Nominal First Hole
<b>Part Name Assigned By Controlling Agency:</b>	Bolt, Tension, Hex Head
<b>Special Features:</b>	Close Tolerance, A286, Cres, Long Thread, Reduced Major Thread Dia, Self Locking And Non Locking 160 Ksi Ftu
<b>Color:</b>	Green Threads
<b>Material:</b>	Iron Alloy 660 Overall
<b>Surface Treatment:</b>	Cadmium And Chromate Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6704D34> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.