

Description

Fastener Length: 3-3/16", Thread: 1/4-28, Thread Length: 27/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	NAS6704D44
Minimum Qty (MOQ):	5 EA
NSN:	5306-01-590-9457
Schedule B:	7318.15.8085
ECCN:	EAR99

NO IMAGE
AVAILABLE

P/N NAS6704D44 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.425 Inches Nominal
Fastener Length:	3.160 Inches Minimum And 3.190 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.125 Inches Minimum And 0.140 Inches Maximum
Width Between Flats:	0.429 Nominal Mils And 0.439 Nominal Centimeters
Grip Diameter:	0.249 Nominal Mils And 0.250 Nominal Centimeters
Shank Unthreaded Hole Diameter:	0.076 Nominal Mils First Hole And 0.086 Nominal Centimeters First Hole
Nominal Thread Diameter:	0.250 Inches
Grip Length:	2.740 Nominal Mils And 2.760 Nominal Centimeters
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	160000 Pounds Per Square Inch
Distance From Head Largest Bearing Surface To Shank Hole Center:	2.997 Inches Nominal First Hole
Part Name Assigned By Controlling Agency:	Bolt, Tension, Hex Head, Close Tolerance, A286 Cres, Long Thread, Reduced Major Thread Dia, Nonlocking 160 Ksi FtU
Color:	Green Threads
Material:	Iron Alloy 660 Overall
Material Document And Classification:	Ams 5731 Assn Std Single Material Response Overall Or Ams 5732 Assn Std Single Material Response Overall Or Ams 5737 Assn Std Single Material Response Overall Or Ams 5853 Assn Std Single Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Ams-qq-p-416, Type II, Class 2 Assn Std Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6704D44> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.