

Description

Fastener Length: 3-7/16", Thread: 1/4-28, Thread Length: 27/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|--------------------|------------------|
| SKU / Model: | NAS6704D48 |
| Minimum Qty (MOQ): | 1 EA |
| NSN: | 5306-01-579-3898 |
| Schedule B: | 7318.15.8085 |
| ECCN: | EAR99 |



* See page 2 for technical characteristics

P/N NAS6704D48 Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.425 Inches Nominal |
| Fastener Length: | 3.410 Inches Minimum And 3.440 Inches Maximum |
| Head Style: | Dished Hexagon |
| Head Height: | 0.125 Inches Minimum And 0.140 Inches Maximum |
| Width Between Flats: | 0.429 Inches Minimum And 0.439 Inches Maximum |
| Grip Diameter: | 0.249 Inches Minimum And 0.250 Inches Maximum |
| Nominal Thread Diameter: | 0.250 Inches |
| Grip Length: | 2.990 Inches Minimum And 3.010 Inches Maximum |
| Thread Quantity Per Inch: | 28 |
| Minimum Tensile Strength: | 160000 Pounds Per Square Inch |
| Part Name Assigned By Controlling Agency: | Bolt, Tension, Hex Head, Close Tolerance, A286 Cres, Long Thread, Reduced Major Thread Dia., Nonlocking, 160 Ksi Ftu |
| Special Features: | Has Drilled Shank, 0.046 In. Dia. Centered 0.178 In. From Screw End |
| Material: | Steel Corrosion Resisting Overall |
| Material Document And Classification: | Uns66286 law Ams5731, Ams5732, Ams5737, Or Ams5853 Assn Std Single Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Ams2700, Method 1, Type 2 Or Type 8, Class 1 Assn Std Single Treatment Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/shear+bolts/NAS6704D48> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.